

مشخصات باکت الواتور تسمه ای آسیای مواد خام خط یک

Raw meal for cement	Bulk	1
62000 mm	C-C	2
1000 mm	Bucket width HC	3
0.65 t/m3	Bulk density	4
580 mm	Bucket spacing	5
69%	Filling rate	6
1.54 m/s	Conveying speed	7
120 °C	Temperature	8
B1600 , 5T : 8P , Vulkan Super Steel wire belt b.w.1050 segment B1600 5T:8P, vulc.S	Steel Belt quality	9
615 m3/hr	Coveying capacity	10
400 t/hr	Conveying capacity	11
0.5%	Moisture	12
0 - 1 mm	Grain size	13
1100 m	Installation height	14
-25 to +35 C	Ambient temperature	15
132 kw	Installed power	16
Siemens (ABB)	Drive motor	17
ELECON KCN 400 S/So	Gear unit with backstop service factor 2.2 acc. To 132 kw	18
ELECON	Auxilliary drive unit	19
with replacable lagging	Drive pully	20
Take up pully - auxiliary drive	Speed monitor	21
Included	belt position monitoring system	22
Included	Fill level indicator	23
voith 487TVG+EEK225M	gearbox put Coupling	24
N-Eupex-coupling A 710 Flender	gearbox out put Coupling	25
Included	Discharge system	26